





8100

Manually operated ANSI 150 carbon steel, Butterfly valve high performance, Wafer style, sizes 2" to 16"

- ISO 5211 direct mounting pad/square stem.
- Compact design, easy access to packin.
- · Replaceable seat design.
- Multiple V-ring stem packing.
- Reliable and consistent torques.
- R.T.F.E. seats (metal seats and API 607 Fire-safe options available upon
- 365 psi max working pressure.
- Temperature range: -76°F to 446°F

G8100: GEAR OPERATED VERSION

NEW

Technical specifications

POSITION	PART NAME	MATERIAL	N.º PIECES
1	BODY	A351-CF8M	1
2	DISC	A240/AISI 316L	1
3	STOP RING	AISI 316L	1
4	SPRING	AISI 316	1

SIZE	ØD	PSI	WEIGHT (LBS)
1/2"	0.91	750	0.24
3/4"	1.10	750	0.40
1"	1.42	750	0.57
1 1/4"	1.97	750	0.88
1 1/2"	2.28	750	1.21
2"	2.80	750	2.20
2 1/2"	3.39	750	3.31
3"	4.13	750	4.41
4"	5.12	750	7.05

WARNING: This product can expose you to chemicals including lead, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.p65warnings.ca.gov.