





100622 LF


PRESS CHECK VALVE


Unibody lead free brass, EURO-PRESS connections, in-line spring loaded check valve.

- Pressure rating size 300 WOG.
- Low cracking pressure 1/2 psi.
- Wide temperature range: -4°F to +210°F.
- Soft seat for bubble tight shutoff, spring loaded for fast seating action.
- · Flow pattern to minimize head loss.
- Perfect sealing both at high and low pressure.
- High technology materials to ensure best resistance in any condition. 100622 LF: size 1/2" to 2".



Technical specifications





POSITION	PART NAME	MATERIAL	N.º PIECES
1	BODY	LF DZR BRASS C27453*	1
2	CHECK VALVE	POM	1
3	O-RING	EPDM	2

* Lead free refers to the wetted surface of pipe, fittings and fixtures in potable water systems that have a weighted average lead content not more than 0.25%. Source: California health & Safety code (116875). Vermont Act 193.

SIZE	Z	L	ØН	CH	CV	PSI	WEIGHT (LBS)
1/2"	0.81	2.22	0.96	-	5.32	200	0.17
3/4"	1.06	2.87	1.24	-	10.17	200	0.31
1"	1.28	3.17	1.50	-	17.34	200	0.49
1 1/4"	1.59	3.64	-	1.89	25.43	200	0.71
1 1/2"	1.59	4.43	-	2.13	36.99	200	1.25
2"	2.20	5.35	-	2.64	63.58	200	1.95

WARNING: This product can expose you to chemicals including lead, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to **www.p65warnings.ca.gov**.

Certifications



HEALTH EFFECTS US-CA NSF3 NSF61

HEALTH EFFECTS